

Technical Data Sheet

TECHNIPOL® PA 2188

DESCRIPTION

TECHNIPOL® PA 2188 is a co-polyamide based thermoplastic adhesive of amber colour, for automotive filter industry. In air engine filter manufacturing it can be used for edge sealing, for reinforcing beads and for pre-filter element bonding. Beside this, in oil engine filter manufacturing it can be used for first/last pleat bonding and for ecological end caps molding. It is characterized by a quick setting time, a good flexibility, a good wettability and a good chemical resistance.


TECHNIPOL® PA 2188 contains more than 80 % of raw materials coming from renewable resources (not-edible).

TECHNICAL CHARACTERISTICS

PROPERTY	TEST METHOD	M.U.	VALUE
Density	ISO 1183	g/cm ³	0,98
Softening point	MI 13	°C	188
Viscosity Brookfield	MI 12	Pa*s	4.0

Cone/ plate Viscometer, Model Brookfield CAP 2000+.

VISCOSITY vs TEMPERATURE CURVE



Technical Data Sheet

TECHNIPOL® PA 2188

PROCESSING CONDITIONS

Suggested temperature profile for extrusion

UNDER HOPPER	FEEDING ZONE	COMPRESSION ZONE	METERING ZONE	EXTRUSION DIE/ HOSE	NOZZLE
50-80 °C	120-150 °C	170-195 °C	195-210 °C	210-220 °C	210-220 °C

Suggested temperature profile for melters

PRE-HEATING GRID	TANK	HOSE	NOZZLE
210-220 °C	215-225 °C	230-240 °C	230-240 °C

PACKAGING

25 kg bags equipped with an aluminum film barrier against moisture action.
500 kg cardboard octabins equipped with an inner PE liner.
500 Kg and 1000 Kg big bags.

STORAGE

Product is stable for 24 months when stored unopened in its original packaging, kept in a cool and dry place and protected from light. When stocked around 5 – 10°C or below, it is recommended to keep it at 15 – 20°C for at least for 24 hours before using it.